

PITSOS PSI09VW32 Nefeli Wall Mounted Air Conditioner, 9000BTU



SKU: IT67309

€389.00

Specifications

Cooling Efficiency

- SEER (Seasonal Energy Efficiency Ratio for cooling): 6.3 W/W
- Energy Class for Cooling: A++
- Cooling Capacity Range: 9000 (3100-11600) BTU/h
- Annual Power Consumption: 156 kWh/year

Heating Efficiency

- Energy Class for Heating (Warmer Season): A+++
- Heating Capacity Range: 10,000 (2,800-11,500) BTU/h
- SCOP (Seasonal Coefficient of Performance for heating) in Warmer Season: 5.1 W/W
- Annual Power Consumption: 714 kWh/year

Technical Specifications

- Airflow Rate (Indoor Unit - Hi/Mi/Lo): 466/360/325 m³/h
- Airflow Rate (Outdoor Unit): 1750 m³/h
- Coverage Area: 12-18 m²
- Dehumidification Capacity: 1.0 liter/hour

General Specifications

- Wi-Fi
- Refrigerant Type: R32
- Home Connect Technology: For remote access and control via a smart app on your smartphone or tablet
- Follow Me Function: Maintains the desired temperature at the location of the remote control
- Silence Mode: Allows the air conditioner to operate quietly
- Low Ambient Temperature Function: Ensures ideal temperature even in extreme environmental conditions
- Function 8°C: Ensures low consumption and stable temperature in the room, even at extreme temperatures environmental conditions
- Ionizer: Removes odors and dust, creating a pleasant and clean environment.
- Cold Catalyst Filter: Captures and removes indoor pollutants like formaldehyde and other harmful gases and odors
- Silver Ion Filter: Neutralizes or inactivates bacteria
- Bio Filter: Provides thorough air purification
- Active Carbon Filter: Traps small dust particles, smoke, pollen, and pet hair
- Self-Cleaning Indoor Unit: Prevents bacterial growth
- Detachable and Washable Front Filter
- Automatic Louvers Positioning: Resets to initial position when the unit is turned on
- Modes: Cooling, Heating, Auto, Fan, Sleep, Dehumidification, Turbo
- LED Display: Indicates the selected temperature on the indoor unit
- Uniform Temperature System: Ensures equal temperature distribution between the ceiling and floor
- Timer: Allows setting the on/off time
- Auto Restart Function: Automatically resumes operation after a power outage
- Fault Detection and Auto Protection: For safety
- 1 Watt Power Consumption in Standby Mode
- Leakage Detection: Optical signal in case of refrigerant leakage
- Remote Control with Digital Display
- Anti Cold Technology: Prevents cold air from entering
- 12-Speed Fan for the Indoor Unit

Noise Level

- Indoor Unit Sound Pressure Level (Hi/Med/Low): 38.5/32/25 dB(A)
- Lowest Indoor Unit Sound Pressure Level: 25 dB(A)
- Indoor Unit Sound Power Level (Hi): 54 dB(A)
- Outdoor Unit Sound Pressure Level: 55.5 dB(A)
- Outdoor Unit Sound Power Level (Hi): 62 dB(A)

Warranty

- Warranty: 10 years

Dimensions & Weight

- Indoor Unit Dimensions (HxWxD): 28.5 x 80.5 x 19.4 cm
- Outdoor Unit Dimensions (HxWxD): 49.5 x 72 x 27 cm
- Indoor Unit Weight: 7.6 kg